



PRODUCT BULLETIN

IN-48

LOW VOC PVC SOLVENT CEMENT for PVC PIPING SYSTEM

GENERAL DESCRIPTION:

IN-48 PVC solvent cement by Hydro & Seal is a grey, low VOC emissions, heavy bodied, medium setting, high strength cement for PVC pipe and fittings with interference fit through 12 inch diameter.

APPLICATION:

This Hydro & Seal IN-48 PVC solvent cement is formulated for all types of PVC piping application with excellent gap filling properties.

NOTE: Hydro & Seal solvent cements must never be used in a PVC system using or being tested by compressed air or gases; including air-over-water booster.

AVAILABILITY:

This product is available in quart, pint, 1/2 pint and 1/4 pint metal cans.

STANDARDS AND CERTIFICATION LISTINGS:

- Meets ASTM D 2564 Standard.
- Meets CSA: B137.3 Standard.
- NSF/ANSI Standard 14 and Standard 61 Listing.
- Compliant with ISO 14001 environmental standard.
- Compliant with Lloyd's Register ISO 9001 Quality Management Systems (QMS).

SPECIFICATIONS:

COLOR:	Grey
RESIN:	PVC
SPECIFIC GRAVITY:	0.946 ± 0.01
BROOKFIELD VISCOSITY:	2,200~3,000 cP @ 73 ± 2°F (23 ± 1°C)

SHELF LIFE:

3 years in tightly sealed containers. The date code of manufacture is stamped on the bottom of the container. Stability of the product is limited by the evaporation of the solvent when the container is opened. Evaporation of solvent will cause the cement to thicken and reduce its effectiveness. Adding of thinners to change viscosity is not recommended and may significantly change the properties of the cement.

QUALITY ASSURANCE:

IN-48 PVC solvent cement by Hydro & Seal is carefully evaluated to assure that consistent high quality is maintained. Gas chromatography, moisture analyzer and additional in depth testing ensures each batch is manufactured to exacting standards. A batch identification code is stamped on each can and assures traceability of all materials and processes used in manufacturing this solvent cement.

SHIPPING:

For One Liter and Above

Proper Shipping Name: Adhesive
Hazard Class: 3
Identification Number: UN 1133
Packing Group: II
Label Required: Flammable Liquid

For Less than One Liter

Proper Shipping Name: Consumer Commodity
Hazard Class: ORM-D



Hydro & Seal UK Corp.
34 Timberline Trail, Aurora, ON L4G 6A5, Canada
Phone: 647-936-9494
Email: info@Hydroandseal.com

SAFETY AND ENVIRONMENTAL PRECAUTIONS:

This product is flammable and considered a hazardous material. In conformance with the Federal Hazardous Substances Labeling Act, the following hazards and precautions are given. Purchasers who repackage this product must also conform to all local, state and federal labeling, safety and other regulations. VOC emissions do not exceed 510 grams per liter.

***DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL.
MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE SKIN OR EYES.***

Keep out of reach of children. Do not take internally. Keep away from heat, spark, open flame and other sources of ignition. Vapors may ignite explosively. Solvent cement vapors are heavier than air and may travel to source(s) of ignition at or near ground or lower level(s) and flash back. Keep container closed when not in use. Store between 40°F (5°C) and 110°F (44°C). Avoid breathing of vapors. Use only in well-ventilated area. If confined or partially enclosed, use forced ventilation. When necessary, use local exhaust ventilation to remove harmful airborne contaminants from employee breathing zone and to keep contaminants below 25 ppm TWA. Atmospheric levels must be maintained below established exposure limits contained in Section II of the Material Safety Data Sheet (MSDS). If airborne concentrations exceed those limits, use of a NIOSH approved organic vapor cartridge respirator with full face-piece is recommended. The effectiveness of an air-purifying respirator is limited. Use it only for a single short-term exposure. For emergency and other conditions where short-term exposure guidelines may be exceeded, use an approved positive pressure self-contained breathing apparatus. Do not smoke, eat or drink while working with this product. Avoid contact with skin, eyes and clothing. May cause eye injury. Protective equipment such as gloves, goggles and impervious apron should be used. Carefully read Material Safety Data Sheet and follow all precautions. Do not use this product for other than intended use. "SARA Title III Section 313 Supplier Notification": This product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (EPCRA) of 1986 and of 40CFR372. This information must be included in all MSDS that are copied and distributed for this material.

FIRST AID:

- Inhalation: If overcome with vapors, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call physician.
- Eye Contact: Flush with plenty of water for 15 minutes and call a physician.
- Skin Contact: Wash skin with plenty of soap and water for at least 15 minutes. If irritation develops, get medical attention.
- Ingestion: If swallowed, give 1 or 2 glasses of water or milk. Do not induce vomiting. Contact physician or poison control center immediately.

IMPORTANT NOTE:

This product is intended for use by skilled individuals at their own risk. These suggestions and data are based on information we believe to be reliable. Installers should verify for themselves that they can make satisfactory joints under varying conditions. Toward this end, it is highly desirable that they receive personal instruction from trained instructors or competent, experienced installers. Contact Hydro & Seal or your supplier for additional information or instructions.

WARRANTY:

Hydro & Seal UK Co. warrants that all new Hydro & Seal products shall be of good quality and free from defects in material and workmanship for the shelf life as indicated on the product. If any Hydro & Seal product becomes defective, or fails to conform to our written limited warranty under normal use and storage conditions, then Hydro & Seal will, without charge, replace the nonconforming product. However, this limited warranty shall not extend to, nor shall Hydro & Seal be responsible for, damages or loss resulting from accident, misuse, negligent use, improper application, or incorporation of Hydro & Seal products into other products. In addition, any repackaging of Hydro & Seal products also shall void the limited warranty. Hydro & Seal shall not be responsible for, nor does this limited warranty extend to, consequential damage, or incidental damage or expense, including without limitation, injury to persons or property or loss of use. Please refer to our standard Hydro & Seal Limited Warranty for additional provisions.



Hydro & Seal UK Corp.
34 Timberline Trail, Aurora, ON L4G 6A5, Canada
Phone: 647-936-9494
Email: info@Hydroandseal.com